

MATERIAL SAFETY DATA SHEET

Date Printed: 10/10/05
Page: 1 of 14
Product Code(s): 6541-G Parts A & B

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: Kwik Fill Polyester Primer Gray Part A

Product Code(s): 6541-G Part A
Manufacturer/Supplier: TRANSTAR AUTOBODY TECHNOLOGIES
2040 Heiserman Dr.
Brighton, MI, 48114, USA

24 Hour Emergency Phone(s): 800-424-9300 (CHEMTREC), 613-996-6666 (CANUTEC)

Business Phone: 810-220-3000

Product Use: Primer

MSDS Prepared By: Kent Lewis

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	EINECS Number	% (by weight)
Styrene	100-42-5	202-851-5	20 - 25
Polyester Resin (Non-Hazardous)	Proprietary	Proprietary	15 - 20
Talc	14807-96-6	238-877-9	15 - 20
Acetone	67-64-1	200-662-2	10 - 15
Titanium Dioxide	13463-67-7	236-675-5	5 - 10
Barium Sulfate	7727-43-7	231-784-4	5 - 10
Magnesite	546-93-0	208-915-9	1 - 5
Quartz (Crystalline Silica)	14808-60-7	238-878-4	0 - 2

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

See Section 15. Regulatory Information for code descriptions
Weight percent (%) of 0.0 means chemical is in trace amounts.

3. HAZARDS IDENTIFICATION

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION.

HMIS Hazard Ratings: Health =2*, Flammability =3, Chemical Reactivity =2

Note: HMIS ratings involve data and interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude

MATERIAL SAFETY DATA SHEET

Date Printed: 10/10/05

Page: 2 of 14

Product Code(s): 6541-G Parts A & B

of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

Potential Health Effects

Acute Effects (Short Term):

Eye: Contact with liquid or vapor may result in irritation, redness, tearing, and blurred vision.

Skin: May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns.

Swallowing: Ingestion of this material may cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Aspiration of this material into the lungs due to vomiting may produce chemical pneumonitis which can be fatal.

Inhalation: Excessive inhalation of vapors may cause nasal and respiratory irritation, acute nervous system depression, fatigue, weakness, nausea, headache, and dizziness. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Chronic Effects of Overexposure (Long Term):

Styrene: Excessive overexposure to styrene has been found to cause the following effects in humans and may aggravate pre-existing disorders of these organs; central nervous system effects, effects on hearing, mild effects on color vision and respiratory tract damage.

Crystalline Silica: Crystalline silica is considered to be hazardous by inhalation, and is a potential human carcinogen (IARC Group 1). The risk depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Crystalline silica may also produce silicosis, which is a non-cancerous lung disease.

Acetone: Overexposure to this material may have effects on the blood and bone marrow.

Cancer Information: The International Agency for Research on Cancer (IARC) has classified styrene as a group 2B carcinogen (possibly carcinogenic to humans). This classification is not based on evidence that styrene may be carcinogenic, but rather on a revised definition for Group 2B, and consideration of new data on styrene oxide (Group 2A). The IARC has classified crystalline silica as a group 1 carcinogen (sufficient evidence of carcinogenicity in humans). This material may contain trace amounts of chemicals considered to be carcinogenic by OSHA, (Benzene, IARC-Group 1, Ethylene Oxide, IARC-Group 1 and N-Nitrosodimethylamine, IARC Group-2A).

Other Health Effects: NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Primary Route(s) of Entry: Inhalation, Skin contact, Eye contact, Ingestion, Skin absorption.

4. FIRST AID MEASURES

Eyes: Flush eyes gently with water for at least 15 minutes. Seek immediate medical attention.

MATERIAL SAFETY DATA SHEET

Date Printed: 10/10/05

Page: 3 of 14

Product Code(s): 6541-G Parts A & B

Skin: Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing: Consult a physician or poison control center immediately. DO NOT INDUCE VOMITING. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. If possible, do not leave individual unattended. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.

Inhalation: If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, oxygen may be beneficial if administered by trained personnel.

5. FIRE FIGHTING MEASURES

Flash Point: 1.4 °F (-17 °C)

Explosive Limit:

Lower: 1.0%

Upper: 12.8%

Autoignition Temperature: 788.0 °F (420.0 °C)

OSHA Flammability Class: Flammable Liquid - Class IB

Hazardous Products of Combustion: May form toxic and corrosive gases: carbon dioxide, carbon monoxide, styrene oxide, nitrogen oxides, and various hydrocarbons.

Fire and Explosion Hazards: Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point.

Extinguishing Media: Regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions: Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus NIOSH approved with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

NFPA Rating: Health - 2, Flammability - 3, Reactivity - 2

6. ACCIDENTAL RELEASE MEASURES

In Case of Spill: Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Ventilate the area. Wear proper protective equipment (Section 8). Avoid breathing vapors. Collect with an inert absorbent and dispose of properly.

For large spills or transportation accidents involving release of this product, contact the Emergency Response Center: 800-424-9300.

Exposure to spilled material may be severely irritating or toxic. Personal protective equipment needs must be evaluated based on information provided and the special circumstances created by the spill including; the material spilled, the

MATERIAL SAFETY DATA SHEET

Date Printed: 10/10/05

Page: 4 of 14

Product Code(s): 6541-G Parts A & B

quantity of the spill, and the area in which the spill occurred. Never exceed any occupational exposure limits. Eliminate all sources of ignition, provide adequate ventilation, dike spill area and add absorbent earth or sawdust to spilled liquid. Sweep up and dispose of in appropriate containers in accordance with Federal, State and/or Local regulations. Do not allow material to enter public sewers or water systems. Dike spill before cleaning up.

7. HANDLING AND STORAGE

Handling: All hazard precautions given in the data sheet must be observed. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Use only with adequate ventilation. Do not breathe sanding dust, vapors or spray mist. Do not take internally. Close container after each use. **Keep out of reach of children.** Use non-sparking tools and explosion proof equipment when handling this material. Containers should be grounded/bonded when pouring. As with all industrial chemicals, use good industrial practices when handling. Avoid eye, skin, and clothing contact. Do not inhale. Do not taste or swallow. Avoid hot surfaces. Use in cool, well-ventilated areas. Keep containers closed when not in use. Keep away from excessive heat and open flames. Do not cut or weld on or near this container. Follow all MSDS/label precautions even after container is emptied because they may retain product residues.

Storage: Store material in a cool, well-ventilated area. For maximum product quality, avoid prolonged storage at temperatures above 75°F (25°C). Do not use or store near heat, sparks, or open flame. Keep container tightly closed. Avoid contact with incompatible materials. Do not reuse container when empty.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection: Chemical splash goggles in compliance with OSHA regulations are recommended.

Skin Protection: Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. A barrier cream may be used for additional skin protection. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection: Use a NIOSH approved respirator designed to remove particulate matter and organic solvent vapors.

Engineering Controls: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below acceptable limits. Explosion-proof ventilation system is acceptable.

Exposure Guidelines:

Hazardous Ingredients	CAS Number	OSHA PEL/TWA	ACGIH TLV
Acetone	67-64-1	1000 ppm	500 ppm
Barium Sulfate	7727-43-7	15 mg/m ³	10 mg/m ³
Crystalline Silica	14808-60-7	N/E	0.05 mg/m ³
Magnesite	546-93-0	15 mg/m ³	10 mg/m ³

MATERIAL SAFETY DATA SHEET

Date Printed: 10/10/05

Page: 5 of 14

Product Code(s): 6541-G Parts A & B

Styrene	100-42-5	100 ppm	20 ppm
Talc	14807-96-6	20 mppcf	2 mg/m ³
Titanium Dioxide	13463-67-7	15 mg/m ³	10 mg/m ³

Mppcf- millions of particles per cubic foot of air N/E-Not Established

Safe Work Practices: Eye washes and safety showers in the workplace are recommended. Avoid contact with skin and eyes. Avoid breathing vapors. Wash hands thoroughly after using and before eating, drinking or smoking. Employee education and training in the safe use and handling of this product is required under the OSHA Hazard Communication Standard 29CFR1200. Smoking in area where this material is used should be strictly prohibited. Always use protective clothing and equipment. Remove all contaminated clothing and wash thoroughly when finished working. Keep food and drink away from material and from area where material is being used.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point:	133 - 293 °F/ 56 -145 °C	Vapor Density:	Heavier than air.
Specific Gravity / Density:	1.37/ 11.4 lbs/gal	Percent Volatiles by weight:	30 - 35 %
Evaporation Rate:	Slower than ethyl ether.	Physical State:	Liquid
Melting Point:	-13 °F / -25 °C	pH:	Neutral
Odor:	Sharp, aromatic odor.	Solubility:	Insoluble in water.
Vapor Pressure:	180 mmHg @ 68 °F/20 °C	Appearance:	Gray Liquid
Octanol/Water Partition Coefficient:		Unknown	
VOC (as packaged-less exempts and water):	3.12 lbs/gal or 375 g/L	VOC (as applied*- 2%by wt hardener- less exempts and water):	1.52 lbs/gal or 182
Percent Solids by weight - as packaged:	65.9 %	Percent Solids by weight - as applied* - 2 % by wt hardener	76.8 %
VHAP Content by weight - as packaged:	20.9 %	VHAP Content by weight - as applied* - 2 % by weight hardener	10.0 %

MATERIAL SAFETY DATA SHEET

Date Printed: 10/10/05

Page: 6 of 14

Product Code(s): 6541-G Parts A & B

***NOTE:** The applied VOC and VHAP Content is lower than the packaged VOC and VHAP Content due to a reactive diluents (styrene) that reacts and becomes non-volatile (bonded in the solid material) when the hardener is added.

10. STABILITY AND REACTIVITY

Hazardous Polymerization: Product may undergo hazardous polymerization if exposed to extreme heat.

Hazardous Decomposition: May form toxic and corrosive gases: carbon dioxide, carbon monoxide, styrene oxide, nitrogen oxides and various hydrocarbons.

Chemical Stability: Stable under normal handling conditions.

Incompatibility: Avoid contact in uncontrolled conditions with: peroxides, strong acids, strong oxidizing agents, halogens, reducing agents and strong bases.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity Data:

Ingredient	CAS #	LD ₅₀ Oral-Rat	LC ₅₀ Inhalation-Rat
Styrene	100-42-5	5,000 mg/kg	24 g/m ³ /4H
Acetone	67-64-1	5,800 mg/kg	50,100 mg/m ³ /8H

N/E-Not Established

Carcinogenicity: See Cancer Information, Section 3.

Mutagenicity: No significant evidence found.

Teratogenicity: No significant risk of birth defects or reproductive toxicity of styrene to humans.

12. ECOLOGICAL INFORMATION

Ecotoxicity: Styrene is toxic to aquatic organisms and should not be released to sewage, draining systems or any body of water exceeding concentrations of approved limits under applicable regulations and permits.

13. DISPOSAL CONSIDERATIONS

RCRA Hazardous Waste: This material as supplied, if discarded, would be regulated as a hazardous waste under RCRA (40 CFR 261). Dispose of in accordance with applicable federal, state, and local regulations.

RCRA Hazard Class: This material would be regulated as EPA Hazardous Waste Number D001 based on the characteristic of ignitability.

MATERIAL SAFETY DATA SHEET

Date Printed: 10/10/05
Page: 7 of 14
Product Code(s): 6541-G Parts A & B

14. TRANSPORT INFORMATION

DOT Description: The DOT Classification for shipping is dependant on quantity, type of packaging (a kit may include other components), or method of shipment.

15. REGULATORY INFORMATION

US Federal Regulations:

TSCA (Toxic Substances Control Act) Status

TSCA (USA) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR 302.4(a)

Component RQ (lbs.)

Styrene 1000

Acetone 5000

SARA Title III: Section 302- Extremely Hazardous Substances

None

SARA Title III: Section 313- Toxic Chemical List

Component CAS Number Percentage

Styrene 100-42-5 20.9 %

EPA Hazardous Air Pollutants (HAPS) 40 CFR 63

Component CAS Number Percentage

Styrene 100-42-5 20.9 %

International Regulations

EINECS (Europe) The intentional ingredients of this product are listed.

DSL (Canada) The intentional ingredients of this product are listed.

WHMIS Classification

Health Hazard: D2A, D2B (Other Toxic Effects)

Physical Hazard: B2 (Flammable)

State and Local Regulations

California Proposition 65:

This product contains the following chemical(s) known to the state of California to cause cancer. BENZENE, STYRENE OXIDE, CARBON BLACK, CRYSTALLINE SILICA, ETHYLENE OXIDE, N-NITROSODIMETHYLAMINE, EPICHLOROXYDRIN

Styrene, in the presence of air and high temperature or prolonged exposure of styrene/air mixture to sunlight, can react to form styrene oxide.

This product contains the following chemical(s) known to the state of California to cause birth defects or reproductive harm. BENZENE, TOLUENE, ETHYLENE OXIDE, EPICHLOROXYDRIN

16. OTHER INFORMATION

Additional Information:

Other Precautions for Use: This product must be mixed with Liquid Activator (MEKP) prior to use. Please refer to the Material Safety Data Sheet (#100636) for catalyst before using. If product is to be sanded, the OSHA PEL/TLV of 10 mg/m³ for nuisance dust should be observed.

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Transtar Autobody Technologies to be accurate.

MATERIAL SAFETY DATA SHEET

Date Printed: 10/10/05

Page: 8 of 14

Product Code(s): 6541-G Parts A & B

As with all chemicals, KEEP AWAY FROM CHILDREN AND ANIMALS. FOR PROFESSIONAL USE ONLY. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

MATERIAL SAFETY DATA SHEET

Date Printed: 10/10/05
Page: 9 of 14
Product Code(s): 6541-G Parts A & B

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: Liquid Activator Part B

Product Code(s): 6541 Activator, Part B
Manufacturer/Supplier: TRANSTAR AUTOBODY TECHNOLOGIES
2040 Heiserman Dr.
Brighton, MI, 48114, USA

24 Hour Emergency Phone(s): 800-424-9300 (CHEMTREC), 613-996-6666 (CANUTEC)

Business Phone: 810-220-3000

Product Use: Polymerization initiator

MSDS Prepared By: Kent Lewis

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	EINECS Number	% (by weight)
Propanoic acid, ester	6846-50-0	229-934-9	60 - 70
Methyl Ethyl Ketone Peroxide	1338-23-4	215-661-2	30 - 35
Hydrogen Peroxide	7722-84-1	231-765-0	0.001 - 3.0
Water	7732-18-5	231-791-2	0.001 - 2.0
Methyl Ethyl Ketone	78-93-3	201-159-0	0.001 - 2.0

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

3. HAZARDS IDENTIFICATION

DANGER! ORGANIC PEROXIDE. HEAT OR CONTAMINATION MAY CAUSE HAZARDOUS DECOMPOSITION. CAUSES EYE AND SKIN BURNS. HARMFUL OR FATAL IF SWALLOWED.

Potential Health Effects

Acute Effects (Short Term):

Eye: Contact with liquid or vapor may result in burns and possibly permanent damage. Symptoms may include burning, redness, tearing, and blurred vision.

Skin: May cause severe skin irritation with blistering. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns.

Swallowing: Ingestion of this material may cause severe gastrointestinal irritation, or burns of the mouth, throat, esophagus and stomach, nausea, diarrhea, and vomiting. Aspiration of this material into the lungs due to vomiting may cause severe lung injury.

MATERIAL SAFETY DATA SHEET

Date Printed: 10/10/05

Page: 10 of 14

Product Code(s): 6541-G Parts A & B

Inhalation: Excessive inhalation of vapors may cause severe nasal and respiratory irritation, acute nervous system depression, fatigue, weakness, nausea, headache, and dizziness. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Chronic Effects of Overexposure (Long Term):

Product: Prolonged and /or repeated inhalation is expected to be severely irritating to the respiratory system.

Methyl Ethyl Ketone: Animal tests show that this substance possibly causes toxic effects upon human reproduction.

Cancer Information: This product does not contain any substance, which is listed as a carcinogen by NTP, IARC or OSHA.

Other Health Effects: NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Primary Route(s) of Entry: Inhalation, Skin contact, Eye contact, Ingestion, Skin absorption.

4. FIRST AID MEASURES

Eyes: Flush eyes gently with water for at least 15 minutes. Seek immediate medical attention. DO NOT let victim rub eyes. Do not attempt to use any neutralization chemicals.

Skin: Immediately remove contaminated clothing. Wash exposed area with soap and water. Seek medical attention. Launder clothing before reuse.

Swallowing: Consult a physician or poison control center immediately. DO NOT INDUCE VOMITING. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. If possible, do not leave individual unattended.

Inhalation: If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, oxygen may be beneficial if administered by trained personnel.

5. FIRE FIGHTING MEASURES

Flash Point: 179.6 °F (82.0 °C)
Explosive Limit: Lower: 2.0% **Upper:** 11.0%
Autoignition Temperature: Not Determined
OSHA Flammability Class: Combustible Liquid - Class IIIA

MATERIAL SAFETY DATA SHEET

Date Printed: 10/10/05

Page: 11 of 14

Product Code(s): 6541-G Parts A & B

Hazardous Products of Combustion: May form toxic and corrosive gases: carbon dioxide, carbon monoxide, water, acetic acid, formic acid, propionic acid, methyl ethyl ketone and various hydrocarbons.

Fire and Explosion Hazards: Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point.

Extinguishing Media: Regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions: Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus NIOSH approved with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

NFPA Rating: Health - 3, Flammability - 2, Reactivity - 2

6. ACCIDENTAL RELEASE MEASURES

In Case of Spill: Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Ventilate the area. Wear proper protective equipment (Section 8). Avoid breathing vapors. Collect with an inert absorbent and dispose of properly.

7. HANDLING AND STORAGE

Handling: All hazard precautions given in the data sheet must be observed. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Use only with adequate ventilation. Do not breathe vapors or spray mist. Do not take internally. Close container after each use. **Keep out of reach of children.**

Storage: Store material in a cool, well-ventilated area. For maximum product quality, avoid prolonged storage at temperatures above 75°F (25°C). To prevent possible self-accelerating decomposition, temperatures in the storage facility must not exceed 131°F (55°C). Do not use or store near heat, sparks, or open flame. Keep container tightly closed. Avoid contact with incompatible materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection: Chemical splash goggles in compliance with OSHA regulations are recommended.

Skin Protection: Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. A barrier cream may be used for additional skin protection. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

MATERIAL SAFETY DATA SHEET

Date Printed: 10/10/05
Page: 12 of 14
Product Code(s): 6541-G Parts A & B

Respiratory Protection: Use a NIOSH approved respirator designed to remove particulate matter and organic solvent vapors.

Engineering Controls: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below acceptable limits. Explosion-proof ventilation system is acceptable.

Exposure Guidelines:

Hazardous Ingredients	CAS Number	OSHA PEL/TWA	ACGIH TLV
Hydrogen Peroxide	7722-84-1	1 ppm	1 ppm
Methyl Ethyl Ketone	78-93-3	200 ppm	200 ppm
Methyl Ethyl Ketone Peroxide	1338-23-4	N/E	0.2 ppm C

Mppcf- millions of particles per cubic foot of air
N/E-Not Established *C*-Ceiling

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point:	176 - 536 °F/ 80 - 280 °C	Vapor Density:	Heavier than air.
Specific Gravity / Density:	1.0/ 8.42 lbs/gal	Percent Volatiles by weight:	Not Available
Evaporation Rate:	Slower than ethyl ether.	Physical State:	Liquid
Melting Point:	32 °F / 0 °C	pH:	Not Determined
Odor:	Ketone odor.	Solubility:	Moderate in water.
Vapor Pressure:	23.2 mmHg @ 68 °F / 20 °C (H ₂ O ₂)	Appearance:	Clear, Colorless Liquid
Octanol/Water Partition Coefficient:	Unknown	VOC (as packaged-less exempts and water):	0.168 lbs/gal or 20 g/L

10. STABILITY AND REACTIVITY

Hazardous Polymerization: Product may undergo hazardous polymerization if exposed to temperatures above 131°F (55°C).

Hazardous Decomposition: May form toxic and corrosive gases: carbon dioxide, carbon monoxide, oxygen, ethane, methane, and various hydrocarbons.

Chemical Stability: Stable under normal handling conditions.

Incompatibility: Avoid contact in uncontrolled conditions with: organic materials, inorganic acids, strong oxidizing agents, accelerators, reducing materials and strong bases.

MATERIAL SAFETY DATA SHEET

Date Printed: 10/10/05
Page: 13 of 14
Product Code(s): 6541-G Parts A & B

11. TOXICOLOGICAL INFORMATION

Acute Toxicity Data:

Ingredient	CAS #	LD ₅₀ Oral-Rat	LC ₅₀ Inhalation-Rat
Methyl Ethyl Ketone Peroxide	1338-23-4	484 mg/kg	200 ppm/4H
Propanoic Acid, ester	6846-50-0	>3,200 mg/kg	N/E
Methyl Ethyl Ketone	78-93-3	2,737 mg/kg	23,500 mg/m ³ /8H

Carcinogenicity: See Cancer Information, Section 3.

Mutagenicity: No significant evidence found.

Teratogenicity: Development inhalation toxicity studies with methyl ethyl ketone in rats and mice resulted in fetal toxicity at maternally toxic doses.

12. ECOLOGICAL INFORMATION

Ecotoxicity: The ecological toxicity of this product is not known.

13. DISPOSAL CONSIDERATIONS

RCRA Hazardous Waste: This material as supplied, if discarded, would be regulated as a hazardous waste under RCRA (40 CFR 261). Dispose of in accordance with applicable federal, state, and local regulations.

RCRA Hazard Class: This material would be regulated as EPA Hazardous Waste Number D001 based on the characteristic of ignitability (oxidizer), D002 based on the characteristic of corrosivity, D003 based on the characteristic of reactivity, U160 (contains MEKP) and D035 (contains MEK).

14. TRANSPORT INFORMATION

DOT Description: The DOT Classification for shipping is dependant on quantity, type of packaging (a kit may include other components), or method of shipment.

15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (USA) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR 302.4(a)

MATERIAL SAFETY DATA SHEET

Date Printed: 10/10/05

Page: 14 of 14

Product Code(s): 6541-G Parts A & B

<u>Component</u>	<u>RQ (lbs.)</u>
------------------	------------------

Methyl Ethyl Ketone Peroxide	10
------------------------------	----

Methyl Ethyl Ketone	5000
---------------------	------

SARA Title III: Section 302- Extremely Hazardous Substances

None

SARA Title III: Section 313- Toxic Chemical List

<u>Component</u>	<u>CAS Number</u>	<u>Percentage</u>
------------------	-------------------	-------------------

Methyl Ethyl Ketone	78-93-3	0.001 - 2.0%
---------------------	---------	--------------

International Regulations

EINECS (Europe) The intentional ingredients of this product are listed.

DSL (Canada) The intentional ingredients of this product are listed.

WHMIS Classification

Health Hazard: C, D2A, E, F (Oxidizer, Toxic Effects, Corrosive, Dangerously Reactive Materials)

Physical Hazard: B3 (Combustible)

State and Local Regulations

California Proposition 65:

This product contains the following chemical(s) known to the state of California to cause cancer. NONE

This product contains the following chemical(s) known to the state of California to cause birth defects or reproductive harm. NONE

16. OTHER INFORMATION

Additional Information:

HMIS Rating: Health - 3, Flammability - 2, Reactivity - 2
Key- 0=Least, 1=Slight, 2=Moderate, 3=Serious, 4=Extreme, *=Chronic Effects

Other Precautions for Use: DO NOT return unused material to the original container. DO NOT contaminate product with foreign materials, it may cause hazardous decomposition. Additional Information may be obtained by calling the Transtar Autobody Technologies at 1-810-220-3000.

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Transtar Autobody Technologies to be accurate. As with all chemicals, KEEP AWAY FROM CHILDREN AND ANIMALS. FOR PROFESSIONAL USE ONLY. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.
