

MATERIAL SAFETY DATA SHEET



Revision 1
Prepared 2009-06-19

Section 1 - Product and Company Identification

Product Name: Euro Clear Activator - Fast

Product Code: 7086, 7088

Manufacturer:
TRANSTAR AUTOBODY TECHNOLOGIES
2040 Heiserman Dr.
Brighton, MI, 48114, USA


24 Hour Emergency Phone(s): 800-424-9300 (CHEMTREC),
613-996-6666 (CANUTEC)
Business Phone: 810-220-3000
Product Use: Activator (Isocyanate)
MSDS Prepared By: Transtar Autobody Technologies

Section 2 - Composition

<u>Chemical Name / CAS No</u>	<u>OSHA Exposure Limits</u>	<u>ACGIH Exposure Limits</u>	<u>Other Exposure Limits</u>
n-Butyl Acetate 123-86-4 40 to 50% Vapor Pressure: 11.5 mmHg	The OSHA legal limit and ACGIH value is 3.5 mg/m3 TWA.	The OSHA legal limit and ACGIH value is 3.5 mg/m3 TWA.	STEL 200ppm
Aliphatic Polyisocyanate 28182-81-2 32 percent Vapor Pressure: 0	None	None: Other 1mg/m3	Chronic inhalation may cause effects similar to those of acute inhalation. Repeated exposure may cause lung irritation, chest pain, and pulmonary edema. Chronic exposure to isocyanates has been reported to cause lung damage, including
Homopolymer of IPDI 53880-05-0 18 percent Vapor Pressure: 36.7 45.0 mm/Hg	None	None	
Aromatic petroleum distillates 64742-95-6 7 percent Vapor Pressure: 2.6 mmHg	None	None	

Section 3 - Hazards Identification

Note: HMIS ratings involve data and interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.



HMIS Rating: 3* - 3 1

Routes of Entry

Inhalation

Skin Contact

Eye Contact

Ingestion

Target Organs

Blood	Eyes	Kidneys	Liver	Lungs	Nervous System	Skin	Other
ACUTE:							
INHALATION - Dizziness, breathing difficulty, headaches, & loss of coordination.							
EYE CONTACT - Moderate irritation, tearing, redness, and blurred vision.							
SKIN CONTACT - Moderate irritant. Can dry and defat skin causing cracks, irritation, and dermatitis.							
INGESTION - Can cause gastrointestinal irritation, vomiting, nausea, & diarrhea.							

Effects of Overexposure, Euro Clear Activator - Fast:

Short Term Exposure The substance irritates the eyes, skin, and respiratory tract. High exposures, above the occupational exposure levels, can cause weakness, headache, and drowsiness and may cause unconsciousness.

Long Term Exposure n-Butyl acetate may cause skin allergy. n-Butyl acetate has been shown to damage the developing fetus in animals. Prolonged and repeated exposure to butyl acetates can cause defatting, drying and cracking of the skin. Although many solvents and petroleum based products cause lung, brain and nerve damage, these chemicals have not been adequately evaluated to determine these effects.

The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by the NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

- None

Section 4 - First Aid Measures

Seek professional medical attention for all over-exposures and/or persistent problems.

INHALATION: Remove person from area to fresh air. If breathing difficulty persists, seek medical attention.

EYE CONTACT: Flush eyes with clean water for a minimum of 15 minutes. Seek medical attention.

SKIN CONTACT: Wash exposed area thoroughly with soap and water.

INGESTION: DO NOT INDUCE VOMITTING. Seek immediate medical attention.

Section 5 - Fire Fighting Measures

Flash Point: 0 C (32 F)

LEL: 1.0 %

UEL: 7.6 %

Extinguishing Media: Foam, Alcohol Foam, CO₂, Dry Chemical, Water Fog, Other.

Unusual Fire and Explosion Hazards: Vapors can travel to a source of ignition and flash back. Closed containers may explode when exposed to extreme heat or burst when contaminated with water (CO₂ gas evolved). Hazards apply to empty containers. Combustion generates toxic fumes.

Hazardous Combustion Products: Carbon monoxide, carbon dioxide, oxides of nitrogen.

Special Firefighting Procedures: Highly toxic fumes may be generated by thermal decomposition. Water runoff from firefighting can cause environmental damage. Dike and collect water used to fight fire.

Fire Equipment: Full fire fighter equipment including SCBA should be worn to avoid skin contact and inhalation of concentrated vapors. Minimize skin exposure.

Section 6 - Accidental Release Measures

For large spills or transportation accidents involving release of this product, contact the Emergency Response Center: 800-424-9300.

Eliminate all sources of ignition, provide adequate ventilation, dike spill area and add absorbent earth or sawdust to spilled liquid. Sweep up and dispose of in appropriate containers in accordance with Federal, State and/or Local regulations

Section 7 - Handling and Storage

Safe Handling Measures: Use non-sparking tools and explosion proof equipment when handling this material. Avoid hot surfaces. Use in cool, well-ventilated areas. Keep containers closed when not in use. Keep away from excessive heat and open flames. Follow all MSDS/label precautions even after container is emptied because they may retain product residues.

Storage Requirements: Store in a cool area away from heat and flames. Do not reuse container when empty.

Section 8 - Exposure Control and PPE

Engineering Controls: General mechanical ventilation or local exhaust should be utilized to keep vapor concentrations below exposure limits (PEL & TLV). Ventilation equipment must be explosion proof.

Safe Work Practices: Eye washes and safety showers in the workplace are recommended. Avoid contact with skin and eyes. Avoid breathing vapors. Wash hands thoroughly after using and before eating, drinking or smoking. Employee education and training in the safe use and handling of this product is required under the OSHA Hazard Communication Standard 29CFR1200. Smoking in area where this material is used should be strictly prohibited. Always use protective clothing and equipment. Remove all contaminated clothing and wash thoroughly when finished working. Keep food and drink away from material and from area where material is being used.

Respiratory Protection: When working with this material use a MSHA/NIOSH approved cartridge respirator or suitable respiratory protection to keep airborne mists and vapor concentrations below the PEL & TLV limits. When using in poorly ventilated and confined spaces, use a fresh-air supplying respirator or a self-contained breathing apparatus.

Eye Protection: Use safety glasses with chemical splash goggles or faceshield.

Skin Protection: Use chemical resistant gloves.

Section 9 - Physical and Chemical Properties

Appearance	Clear, colorless
Odor	Organic solvent
Physical State	Liquid
Vapor Density	Heavier than air
Vapor Density	3.70
Boiling Range	98 to 194 C
Specific Gravity (SG)	1.002
Lbs VOC/Gal (- H ₂ O & Ex Solv)	4.17
Lbs VOC/Gal	4.17

Section 10 - Stability and Reactivity

Incompatible with:

- Strong oxidizers
- Strong oxidizing agents
- Carbon Monoxide, Carbon Dioxide

Hazardous products produced under decomposition:

- Carbon Monoxide, Carbon Dioxide
- Oxides of nitrogen, hydrogen cyanide

Section 11 - Toxicological Information

This material has not been tested for toxicological effects.

Section 12 - Ecological Information

This material has not been tested for ecological effects.

Section 13 - Disposal Considerations

Subject to hazardous waste generation, treatment, storage and disposal under RCRA, 40CFR261. Product should be disposed of in accordance with all Federal, State and local regulations.

Section 14 - Transportation Information

The following transportation information is provided based on Transtar Autobody Technologies interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking and labeling prior to offering for transport.

USA (DOT) Status: UN1263, Paint Related Material, 3, PG III; For inner packagings not exceeding 5 L each packaged in a strong outer box: CONSUMER COMMODITY ORM-D

Water (IMDG) Status: UN1263, Paint related material, 3, PG III

Air (ICAO,IATA) Status: UN1263, Paint related material, 3, PG III

Canada (TDG) Status: UN1263, Paint Related Material, 3, PG III ; For inner packagings not exceeding 5 L each packaged in a strong outer box: CONSUMER COMMODITY ORM-D

Section 15 - Regulatory Information

The information listed in this section is not all inclusive of all regulations for this product or the chemical components of this product.

The chemicals are require to be reported for Prop 65

-None

DSL Status: Except for the following chemicals listed below all chemicals are on the DSL Inventory and or are in compliance with the DSL

-None

EINECS : Except for the following chemicals listed below all chemicals are listed in EINICS and or are in compliance with the DSL

-None

The following chemicals are listed under Massachusetts RTK:

123-86-4 n-Butyl Acetate 40 to 50 percent
28182-81-2 Aliphatic Polyisocyanate 32 percent
53880-05-0 Homopolymer of IPDI 18 percent
64742-95-6 Aromatic petroleum distillates 7 percent

New Jersey RTK

123-86-4 n-Butyl Acetate 40 to 50 percent
28182-81-2 Aliphatic Polyisocyanate 32 percent
53880-05-0 Homopolymer of IPDI 18 percent
64742-95-6 Aromatic petroleum distillates 7 percent

Pennsylvania RTK

123-86-4 n-Butyl Acetate 40 to 50 percent
28182-81-2 Aliphatic Polyisocyanate 32 percent
53880-05-0 Homopolymer of IPDI 18 percent
64742-95-6 Aromatic petroleum distillates 7 percent

Rhode Island RTK

123-86-4 n-Butyl Acetate 40 to 50 percent
64742-95-6 Aromatic petroleum distillates 7 percent

SARA 312

64742-95-6 Aromatic petroleum distillates 7 percent

Section 313 of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This Product contains a chemical or chemicals which are subject to the reporting requirements of the Act, and Title 40 of the Code of Federal Regulations part 372.

-None

WHMIS:

B2 D1A D2A D2B

The following are not listed under TSCA or do not meet the reporting/listing requirements under TSCA

- None

Section 16 - Other Information

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Transtar Autobody Technologies to be accurate. As with all chemicals, KEEP AWAY FROM CHILDREN AND ANIMALS. FOR PROFESSIONAL USE ONLY. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.