

MATERIAL SAFETY DATA SHEET

PAGE 1

PRODUCT CODE:KAI 2000

PRODUCT NAME: ULTRA CLEAR

=====SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: TAMCO
ADDRESS : 431 WEST 25TH STREET
NORFOLK, VA 23517

INFORMATION PHONE : 757-627-9551
EMERGENCY PHONE : 800-424-9300

=====SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION=====

EXPORTABLE COMPONENTS	CAS #	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
TBAC OSHA PEL: 200 ppm ACGIH TLV: 435Mg/M ³ HAPS NONE	540-88-5	10 100F	30-45
METHYL NORMAL AMYL KETONE OSHA PEL: 100 ppm ACGIH TLV: 233 Mg/M ³ HAPS NONE	110-43-0	2.14 68F	<5%
ACETONE OSHA PEL: 750 ppm ACGIH TLV: 1780 Mg/M ³ HAPS NONE	67-64-1	181.7 68F	10-15

Toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.
NOTE: Dry film may present a hazard if sanded or abraded in the form of a nuisance particle. ACGIH TLV: 10 Mg/M³

=====SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS=====

BOILING RANGE: 133°F – 282°F	SPECIFIC GRAVITY (H₂O=1 g/L): 0.93
VAPOR DENSITY: GREATER THAN AIR	WEIGHT/GAL.: 7.70 lb/Gal
%VOLATILES (VOLUME): 73.1%	%SOLIDS (WT): 30.7%
COATING VOC: 1.0 lb/Gal	SOLUBILITY IN WATER: NEGL.
APPEARANCE AND ODOR: CLEAR, OF SOLVENT	EVAPORATION RATE: N/A

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: VENTILATE SPILL AREA. ELIMINATE ALL SOURCES OF IGNITION. CONFINE SPILL AS QUICKLY AS POSSIBLE. ABSORB WITH OIL ABSORBING COMPOUND, AND SCOOP UP FOR DISPOSAL.

PAGE 3

WASTE DISPOSAL METHOD: TO MEET FEDERAL, STATE, OR LOCAL ENVIRONMENTAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME AND/OR STRONG OXODANTS. TO REDUCE FIRE OR EXPLOSION RISK FROM STATIC ACCUMULATION DISCHARGE, EFFECTIVELY GROUND PRODUCT TRANSFER SYSTEM IN ACCORDANCE WITH NFPA STANDARD FOR PETROLEUM PRODUCTS.

OTHER PRECAUTIONS: N/A

=====SECTION VIII - CONTROL MEASURES=====

RESPIRATORY PROTECTION: A POSITIVE PRESSURE SUPPLIED AIR RESPIRATOR IS MANDATORY. OBSERVE OSHA REGULATIONS FOR RESPIRATOR USE (29 CFR 1910.134).

VENTILATION: TO MEET FEDERAL, STATE, OR LOCAL ENVIRONMENTAL REGULATIONS. LOCAL EXHAUST: OVER 60 FPM RECOMMENDED.

PROTECTIVE GLOVES: NEOPRENE, COMPLIANCE: CFR-170-179

EYE PROTECTION: SAFETY GLASSES, COMPLIANCE: ANSI Z87.1-1989, CSA Z94.3-M88

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: LEATHER BOOTS, COMPLIANCE: ANSI Z41 PT 91 MI/75 C/75

WORK/HYGIENIC PRACTICES: AVOID PROLONGED OR REPEATED CONTACT IN ANY FORM. THOROUGHLY CLEAN, DRY, AND/OR WASH ANY CONTAMINATED WORKING APPAREL BEFORE REUSE. CLEANSE ANY CONTACTED SKIN AREAS THOROUGHLY AT THE END OF EACH WORK PERIOD, ALSO BEFORE BREAKS AND MEALS. USE NECESSARY PROTECTIVE EQUIPMENT AND MAINTAIN UPKEEP FOR EFFECTIVENESS.

=====SECTION IX - DISCLAIMER=====

THE COMPONENTS OF THIS PRODUCT ARE LISTED ON THE EPA/TSCA INVENTORY OF CHEMICAL SUBSTANCES. TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE AND OBTAINED FROM SOURCES BELIEVED BY HARPEA, INC. TO BE ACCURATE.