MATERIAL SAFETY DATA SHEET

HMIS Ratings
Health 2
Flammability 2
Reactivity 0
Protection X

Chemical Product and Company Identification

Manufactured For Klingspor Abrasives Inc.

PO Box 2367 Hickory, NC 28602

Phone (828) 322-3030

Emergency Phone CHEMTREC

1-800-424-9300

FOR INTERNATIONAL CALLS

(703) 527-3887

Date Modified 12/21/10

Product Identity Max Cut Compound

Product Use Automotive Reconditioning Product

Composition / Information on Ingredients

Ingredient Name	CAS Number	% (By Weight)
Water	7732-18-5	29.0 - 39.0
Light Aliphatic Solvent Naphtha (Petroleum)	64742-89-8	12.0 – 22.0
Silica, Crystalline		10.0 – 20.0
Silica		5.0 – 15.0
Hydrocarbon Liquid	64742-47-8	2.3 - 12.0
Silica	7631-86-9	1.0 – 10.0
Aliphatic Petroleum Distillates	8042-47-5	1.0 - 9.0
Glycerine	56-81-5	1.0 - 9.0
Tall Oil Fatty Acid	61790-12-3	1.0 - 7.0
Morpholine	110-91-8	1.0 - 6.0

Hazards Identification

Potential Health Effects

Skin Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

Eyes This product may be severely irritating to the eyes. Symptoms include itching, burning, redness and tearing.

Inhalation This product may cuase irritation to the respiratory system.

Ingestion Ingestion of this product may cause nausea, vomiting and diarrhea.

Hazard Statements

FLAMMABLE

CAUTION: EYE AND SKIN IRRITANT

First Aid Measures

First Aid

Skin Immediately take off all contaminated clothing. For skin contact, wash immediately with soap

and water. If irritation persists, get medical attention.

Eyes Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.

Inhalation If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give

oxygen.

Ingestion If the material is swallowed, get immediate medical attention or advice – Do not induce vomiting.

Fire Fighting Measures

Hazardous Combustion Products

Carbon monoxide, carbon dioxide and other hydrocarbon fragments.

Extinguishing Media

Alcohol foam. Carbon dioxide, dry chemical or water.

General Fire Hazards

This product is combustible at high temperatures. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective clothing including self contained breathing apparatus.

Flash Point 84° F PM lowest flashing component

Flammability Limits in Air, Lower, % by Volume 0.7%

Flammability Limits in Air, Upper, % by Volume 6%

Accidental Release Measures

Containment Procedures

Eliminate sources of ignition. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

Clean-Up Procedures

Absorb spill with inert material. Shovel material into appropriate container for disposal.

Handling and Storage

Handling Procedures

Avoid prolonged or repeated skin contact with this material. Keep this product from heat, sparks, or open flame.

Storage Procedures

Keep the container tightly closed and in a cool, well-ventilated place. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit. Do not freeze.

Exposure Controls / Personal Protection

Engineering Controls

Explosion proof exhaust ventilation should be used.

Personal Protective Equipment

Eyes/Face

Wear chemical goggles.

Skin

Use impervious gloves. Use of impervious apron and boots are recommended.

Respiratory

If ventilation is not sufficient to effectively prevent buildup of vapor/mist/fume/dust, appropriate NIOSH/MSHA respiratory protection must be provided.

General

Use good industrial hygiene practices in handling this material. Eye wash fountain and emergency showers are recommended.

Physcial & Chemical Properties

Boiling Point >212 F

Specific Gravity 1.145

Vapor Pressure <20 mm/Hg

Solubility (H2O) Dispersible

pH 8.5

Freezing Point 32 F

Chemical Stability & Reactivity Information

Chemical Stability

Stable under normal conditions.

Hazardous Decomposition

Hazardous combustion products may include carbon monoxide, carbon dioxide and hydrocarbon fragments.

Hazardous Polymerization

Will not occur.

Incompatibility

Strong oxidizing agents (peroxides, chlorine, strong acids).

Toxicological Information

Toxicological Information

No data available for this product.

Ecological Information

Ecological Information

No data available for this product.

Disposal Considerations

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Transporation Information

US DOT HMR INFORMATION

Proper Shipping Name flammable liquid, nos (Petroleum Distillates)

Identification Number UN1993 Packaging Group II

Hazard Class 3

Regulatory Information

STATE REGULATIONS

California – Proposition 65 – Carcinogens List SILICA, CRYSTALLINE SILICA-TRIPOLI OGR

Other Information

Disclaimer

NOTICE: The information presented herein is based on data considered to be accurate as of the date of preparation of this Material Safety Data Sheet. However, MSDS may not be used as a commercial specification sheet of manufacturer or seller, and no warranty or representation, expressed or implied, is made as to the accuracy or comprehensiveness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Prepared By Technical Department

Issue Date 12/21/2010