

MATERIAL SAFETY DATA SHEET

Date Prepared: 1/23/07
Everglaze

Page: 1
MSDS Number: 110001

SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: Everglaze Spot Putty
Product Numbers: 100403
Product Use: Nitrocellulose Spot Putty

Emergency Telephone Numbers:

Fibre Glass-Evercoat CHEMTREC: 1-800-424-9300
a Division of Illinois Tool Works Inc. CANUTEC: 1-613-996-6666
6600 Cornell Road
Cincinnati, Ohio USA
Phone: 513-489-7600

Prepared By: Safety Department

SECTION 2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	EINECS Number	% (by weight)
Talc	14807-96-6	238-877-9	35 – 45
Calcium Carbonate	1317-65-3	215-279-6	15 – 25
Toluene	108-88-3	203-625-9	10 – 25
Nitrocellulose	9004-70-0	N/L	1 – 5
n-Butyl Acetate	123-86-4	204-658-1	1 – 5
Di-2-Ethylhexyl Phthalate	117-81-7	204-211-0	1 – 5
Iron Oxide	1309-37-1	215-168-2	1 – 5
Isopropyl Alcohol	67-63-0	200-661-7	1 – 5
Xylene	1330-20-7	215-535-7	1 – 5
Isobutyl Acetate	110-19-0	203-745-1	1 – 5
Methyl Ethyl Ketone	78-93-3	201-159-0	0 – 2
Amorphous Silica	7631-86-9	231-545-4	0 – 2
Ethyl Benzene	100-41-4	202-849-4	0 – 2

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

SECTION 3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING! FLAMMABLE LIQUID AND VAPOR. VAPOR HARMFUL. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION.

Potential Health Effects

Acute Effects (Short Term):

Eye: Contact with liquid or vapor may result in irritation, redness, tearing, and blurred vision.

MATERIAL SAFETY DATA SHEET

Date Prepared: 1/23/07

Page: 2

Everglaze

MSDS Number: 110001

- Skin:** May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns.
- Swallowing:** Ingestion of this material may cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Aspiration of this material into the lungs due to vomiting may produce chemical pneumonitis which can be fatal.
- Inhalation:** Excessive inhalation of vapors may cause nasal and respiratory irritation, acute nervous system depression, fatigue, weakness, nausea, headache, and dizziness. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Chronic Effects of Overexposure (Long Term):

- Toluene:** Possible birth defects hazard. Toluene may be harmful to the human fetus based on positive results with laboratory animals. Overexposure to Toluene has been suggested as a cause of the following effects in humans: cardiac sensitization, kidney damage. The substance may have effects on the central nervous system, resulting in decreased learning ability and psychological disorders.
- Di-2-Ethylhexyl Phthalate:** This substance may be a carcinogenic risk to humans based on animal data. Possible birth defects hazard.
- Methyl Ethyl Ketone:** Animal tests show toxic effects upon human reproduction.
- Xylene:** The substance may have effects on the central nervous system, resulting in decreased learning ability.

Cancer Information: The IARC has classified ethyl benzene as a group 2B carcinogen (possibly carcinogenic to humans) based on the increase of kidney tumors in rats and an increase in lung and liver cancer in mice. This material may contain trace amounts of chemicals considered to be carcinogenic by OSHA (Benzene, IARC-Group 1).

Other Health Effects: NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Primary Route(s) of Entry: Inhalation, Skin contact, Eye contact, Ingestion, Skin absorption.

SECTION 4. FIRST AID MEASURES

- Eyes:** Flush eyes gently with water for at least 15 minutes. Seek immediate medical attention.

MATERIAL SAFETY DATA SHEET

Date Prepared: 1/23/07

Page: 3

Everglaze

MSDS Number: 110001

- Skin:** Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.
- Swallowing:** Consult a physician or poison control center immediately. DO NOT INDUCE VOMITING. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. If possible, do not leave individual unattended.
- Inhalation:** If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, oxygen may be beneficial if administered by trained personnel.

SECTION 5. FIRE FIGHTING MEASURES

Flash Point: 25 °F (-4 °C)

Explosive Limit: Lower: 1.0% Upper: 12.7%

Autoignition Temperature: 662.0 °F (350.0 °C)

OSHA Flammability Class: Flammable Liquid – Class IB

Hazardous Products of Combustion: May form toxic and corrosive gases: carbon dioxide, carbon monoxide, nitrogen oxides and various hydrocarbons.

Fire and Explosion Hazards: Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point.

Extinguishing Media: Regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions: Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus NIOSH approved with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

NFPA Rating: Health - 2, Flammability - 3, Reactivity - 0

SECTION 6. ACCIDENTAL RELEASE MEASURES

In Case of Spill: Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Ventilate the area. Wear proper protective equipment (Section 8). Avoid breathing vapors. Collect with an inert absorbant and dispose of properly.

SECTION 7. HANDLING AND STORAGE

MATERIAL SAFETY DATA SHEET

Date Prepared: 1/23/07
Everglaze

Page: 4
MSDS Number: 110001

Handling: All hazard precautions given in the data sheet must be observed. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Use only with adequate ventilation. Do not breathe sanding dust, vapors or spray mist. Do not take internally. Close container after each use. **Keep out of reach of children.**

Storage: Store material in a cool, well-ventilated area. For maximum product quality, avoid prolonged storage at temperatures above 75°F (25°C). Do not use or store near heat, sparks, or open flame. Keep container tightly closed. Avoid contact with incompatible materials.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection: Chemical splash goggles in compliance with OSHA regulations are recommended.

Skin Protection: Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. A barrier cream may be used for additional skin protection. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection: Use a NIOSH approved respirator designed to remove particulate matter and organic solvent vapors.

Engineering Controls: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below acceptable limits. Explosion-proof ventilation system is acceptable.

Exposure Guidelines:

<u>Hazardous Ingredients</u>	<u>CAS Number</u>	<u>OSHA PEL/TWA</u>	<u>ACGIH TLV</u>
Calcium Carbonate	1317-65-3	15 mg/m ³	10 mg/m ³
Di-2-Ethylhexyl Phthalate	117-81-7	N/E	5 mg/m ³
Iron Oxide	1309-37-1	10 mg/m ³	5 mg/m ³
Isopropyl Alcohol	67-63-0	400 ppm	400 ppm
Methyl Ethyl Ketone	78-93-3	200 ppm	200 ppm
n-Butyl Acetate	123-86-4	150 ppm	150 ppm
Talc	14807-96-6	20 mppcf	2 mg/m ³
Toluene	108-88-3	200 ppm	50 ppm
Amorphous Silica	7631-86-9	20 mppcf	N/E
Xylene	1330-20-7	100 ppm	100 ppm
Isobutyl Acetate	110-19-0	150 ppm	150 ppm
Ethyl Benzene	100-41-4	100 ppm	100 ppm

Mppcf- millions of particles per cubic foot of air N/E-Not Established

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

MATERIAL SAFETY DATA SHEET

Date Prepared: 1/23/07
Everglaze

Page: 5
MSDS Number: 110001

Boiling Point:	176 - 259 °F / 80 - 126 °C	Vapor Density:	Heavier than air.
Specific Gravity / Density:	1.57/ 13.08 lbs/gal	Percent Volatiles by weight:	25 - 30 %
Evaporation Rate:	Slower than ethyl ether.	Physical State:	Paste
Melting Point:	-58.0 °F / -50.0 °C	pH:	Neutral
Odor:	Sharp, aromatic odor.	Solubility:	Insoluble in water.
Vapor Pressure:	71 mmHg @ 68 °F / 20 °C (MEK)	Appearance:	Red Paste
Octanol/Water Partition Coefficient:	Unknown	VOC (material – less exempts and water):	3.5 lbs/gal or 420 g/L

SECTION 10. STABILITY AND REACTIVITY

Hazardous Polymerization: Product will not undergo hazardous polymerization.

Hazardous Decomposition: May form: carbon dioxide, carbon monoxide, nitrogen oxides and various hydrocarbons.

Chemical Stability: Stable under normal handling conditions.

Incompatibility: Avoid contact in uncontrolled conditions with: strong oxidizing agents, acids, alkalis and halogens.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute Toxicity Data:

Ingredient	CAS #	LD₅₀ Oral-Rat	LC₅₀ Inhalation-Rat
Toluene	108-88-3	5,000 mg/kg	N/E
n-Butyl Acetate	123-86-4	13,100 mg/kg	2,000 ppm/4H
Calcium Carbonate	1317-65-3	6,450 mg/kg	N/E
Methyl Ethyl Ketone	78-93-3	2,737 mg/kg	23,500 mg/m ³ /8H
Isopropyl Alcohol	67-63-0	5,045 mg/kg	N/E
Di-2-Ethylhexyl phthalate	117-81-7	30,600 mg/kg	N/E
Xylene	1330-20-7	4,300 mg/kg	5,000 ppm/4H
Isobutyl Acetate	110-19-0	13,400 mg/kg	N/E
Ethyl Benzene	100-41-4	3,500 mg/kg	N/E

Carcinogenicity: See Cancer Information, Section 3.

Mutagenicity: No significant evidence found.

MATERIAL SAFETY DATA SHEET

Date Prepared: 1/23/07

Page: 6

Everglaze

MSDS Number: 110001

Teratogenicity: Possible birth defects hazard. Toluene and Methyl Ethyl Ketone may be harmful to the human fetus based on positive results with laboratory animals.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity: This material should not be released to sewage, draining systems or any body of water exceeding concentrations of approved limits under applicable regulations and permits.

SECTION 13. DISPOSAL CONSIDERATION

RCRA Hazardous Waste: This material as supplied, if discarded, would be regulated as a hazardous waste under RCRA (40 CFR 261). Dispose of in accordance with applicable federal, state, and local regulations.

RCRA Hazard Class: This material would be regulated as EPA Hazardous Waste Number D001 based on the characteristic of ignitability.

SECTION 14. TRANSPORT INFORMATION

DOT Description: The DOT Classification for shipping is dependant on quantity, type of packaging or method of shipment.

SECTION 15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (USA) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR 302.4(a)

<u>Component</u>	<u>RQ (lbs.)</u>
Toluene	1000
Methyl Ethyl Ketone	5000
n-Butyl Acetate	5000
Di-2-Ethylhexyl phthalate	100
Xylene	100
Isobutyl Acetate	5000
Ethyl Benzene	1000

SARA Title III: Section 302- Extremely Hazardous Substances
None

SARA Title III: Section 313- Toxic Chemical List

MATERIAL SAFETY DATA SHEET

Date Prepared: 1/23/07

Page: 7

Everglaze

MSDS Number: 110001

<u>Component</u>	<u>CAS Number</u>	<u>Percentage</u>
Toluene	100-42-5	10 - 25 %
Di-2-Ethylhexyl phthalate	117-81-7	1 - 5%
Methyl Ethyl Ketone	78-93-3	0 - 2%
Isopropyl Alcohol	67-63-0	1 - 5 %
Xylene	1330-20-7	1 - 5%
Ethyl Benzene	100-41-4	0 - 2%

International Regulations

EINECS (Europe) The intentional ingredients of this product are listed.

DSL (Canada) The intentional ingredients of this product are listed.

WHMIS Classification

Health Hazard: D2A, D2B (Other Toxic Effects)

Physical Hazard: B2 (Flammable)

State and Local Regulations

California Proposition 65:

This product contains the following chemical(s) known to the state of California to cause cancer. DI-2-ETHYLHEXYL PHTHALATE, BENZENE

This product contains the following chemical(s) known to the state of California to cause birth defects or reproductive harm. TOLUENE, BENZENE

SECTION 16. OTHER INFORMATION

HMIS Rating: Health - 2*, Flammability - 3, Reactivity - 0
Key- 0=Least, 1=Slight, 2=Moderate, 3=Serious, 4=Extreme, *=Chronic Effects

Other Precautions for Use: If product is to be sanded, the OSHA PEL/TLV of 10 mg/m³ for nuisance dust should be observed.

Additional Information may be obtained by calling the Evercoat MSDS Hotline at 1-800-729-7600.

NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances.