

Date Printed: 12/12/2007  
Product Code(s): 1221, 1225, 1229

Page: 1

---

### 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: Hydroflex Super Hi-Build

Product Code(s): 1221, 1225, 1229

Manufacturer/Supplier: TRANSTAR AUTOBODY TECHNOLOGIES  
2040 Heiserman Dr.  
Brighton, MI, 48114, USA

24 Hour Emergency Phone(s): 800-424-9300 (CHEMTREC), 613-996-6666 (CANUTEC)

Business Phone: 810-220-3000

Product Use: Primer

MSDS Prepared By: Transtar Autobody Technologies

---

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% by Weight
Talc	14807-96-6	15- 25%
Acrylic Polymer	Non Hazard	10- 15%
Barium Sulfate	7727-43-7	5 - 10%
* Ethylene Glycol Monobutyl Ether	111-76-2	5 - 10%
* n-Methyl Pyrrolidone	872-50-4	0 - 5%
* Diethylene Glycol n-Butyl Ether	112-34-5	0 - 5%

See Section 15. Regulatory Information for code descriptions  
Weight percent (%) of 0.0 means chemical is in trace amounts.

---

### 3. HAZARDS IDENTIFICATION

CAUTION! COMBUSTIBLE IRRITANT.

HMIS Hazard Ratings: Health =1 , Flammability =1, Chemical Reactivity =0

Note: HMIS ratings involve data and interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

#### Potential Health Effects

Eyes: Minimal to slight irritation to the eyes. Exposure can cause redness and itching.

Skin: Slight irritation to the skin. Can be absorbed through the skin. Prolonged contact with this product can cause reddening, swelling, rash scalling or blistering.

Inhalation: Minimal to slight irritation to the respiratory system. Dust

Date Printed: 12/12/2007  
Product Code(s): 1221, 1225, 1229

Page: 2

---

from sanding may contain respirable size particles which can be irritating or damaging to the respiratory tract and lungs.

Ingestion: Slight irritation to the digestive tract.

---

#### 4. FIRST AID MEASURES

Seek professional medical attention for all over-exposures and/or persistent problems.

Eyes Contact: Flush eyes with clean water for a minimum of 15 minutes. Seek medical attention.

Skin Contact: Wash exposed area thoroughly with soap and water.

Inhalation: Remove person from area to fresh air. If breathing difficulty persists, seek medical attention.

Ingestion: DO NOT INDUCE VOMITTING. Seek immediate medical attention.

---

#### 5. FIRE FIGHTING MEASURES

##### Flammable Properties

Flash Point: >212 Deg F, 100 Deg C  
Method: TCC  
Upper Explosive Limit (UEL): 24.6  
Lower Explosive Limit (LEL): .85  
Autoignition Temperature: No data

Extinguishing Media: Foam, Alcohol Foam, CO<sub>2</sub>, Dry Chemical, Water Fog, Other.

Special Firefighting Procedures: Full fire fighter equipment including SCBA should be worn to avoid skin contact and inhalation of concentrated vapors. Minimize skin exposure. Highly toxic fumes may be generated by thermal decomposition. Water runoff from firefighting can cause environmental damage. Dike and collect water used to fight fire.

Hazardous Combustion Products: Carbon monoxide, carbon dioxide, oxides of nitrogen.

Unusual Fire and Explosion Hazards: Closed containers may explode when exposed to extreme heat or burst when contaminated with water (CO<sub>2</sub> gas evolved). Hazards apply to empty containers. Combustion generates toxic fumes.

---

#### 6. ACCIDENTAL RELEASE MEASURES

For large spills or transportation accidents involving release of this product, contact the Emergency Response Center: 800-424-9300.

This material is not flammable or combustible. A spill of this material should be treated with care. Eliminate all sources of

Date Printed: 12/12/2007  
 Product Code(s): 1221, 1225, 1229

Page: 3

---

ignition, provide adequate ventilation, dike spill area and add absorbent earth or sawdust to spilled liquid. Sweep up and dispose of in appropriate containers in accordance with Federal, State and/or Local regulations.

---

#### 7. HANDLING AND STORAGE

Use in cool, well-ventilated areas. Keep containers closed when not in use. Keep away from incompatibles. Keep away from excessive heat and open flames. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Store in a cool area away from heat and flames. Do not reuse container when empty.

---

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

##### Exposure Guidelines

Chemical Name/Exposure Limits	CAS Number
Talc	14807-96-6
OSHA PEL: 20 mppcf; ACGIH TLV: 2 mg/m <sup>3</sup>	
Acrylic Polymer	Non Hazard
OSHA PEL: NA, ACGIH TLV: NA, OTHER: NA	
Barium Sulfate	7727-43-7
OSHA PEL: 5mg/m <sup>3</sup> (resp) 15mg/m <sup>3</sup> (total), ACGIH TLV: 10mg/m <sup>3</sup>	
* Ethylene Glycol Monobutyl Ether	111-76-2
OSHA PEL: 50ppm, ACGIH TLV: 20ppm	
* n-Methyl Pyrrolidone	872-50-4
OSHA PEL: NA, ACGIH TLV: NA, OTHER: 100 ppm	
* Diethylene Glycol n-Butyl Ether	112-34-5

Engineering Controls: Engineering controls should be utilized to control airborne contaminants below exposure limits (PEL & TLV). Ventilation equipment must be explosion proof. Use exhaust if general ventilation is not sufficient to keep the airborne contaminant levels low.

Respiratory Protection: Utilize engineering controls to reduce emission levels below the time weighted exposure limits (ACGIH TLV & OSHA PEL). Wear an approved respirator if exposure limits are above the exposure limits listed above. When spraying this material utilize engineering controls such as vents and fans, to reduce emission levels below the time weighted exposure limits (ACGIH TLV & OSHA PEL) or use a fresh-air supplying respirator or a self-contained breathing apparatus (SCBA).

Eye Protection: Use safety glasses or splash goggles.

Skin Protection: Use chemical resistant gloves.

Safe Work Practices: Eye washes and safety showers in the workplace are recommended. Avoid contact with skin and eyes. Avoid breathing

Date Printed: 12/12/2007  
Product Code(s): 1221, 1225, 1229

Page: 4

---

vapors. Wash hands thoroughly after using and before eating, drinking or smoking. Employee education and training in the safe use and handling of this product is required under the OSHA Hazard Communication Standard 29CFR1200. Smoking in area where this material is used should be strictly prohibited. Always use protective clothing and equipment. Remove all contaminated clothing and wash thoroughly when finished working. Keep food and drink away from material and from area where material is being used.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Homogeneous mixture  
Physical State: Liquid  
Color: Black  
Odor: Slight glycol ether  
Odor Threshold: No Data  
Specific Gravity (water=1) 1.30  
Vapor Pressure: No data  
Vapor Density: Heavier than air  
Material VOC: 0.95 lb/gl 114 g/l  
Coating VOC: 1.54 lb/gl 184 g/l  
Evaporation Rate: Faster than Butyl Acetate  
Boiling Point: 339 deg F  
Melting Point: No data  
Freezing Point: No data  
Viscosity at Ambient Temperature: No data  
Solubility in Water: Partial  
Octanol/Water Partition Coefficient: No data  
pH: No data

---

## 10. STABILITY AND REACTIVITY

Stability: Stable

Incompatibility: Strong acids, strong bases and strong oxidizing agents.

Hazardous Polymerization: Will not occur.

---

## 11. TOXICOLOGICAL INFORMATION

### Effects of Exposure:

Spraying of material can cause an oxygen deficient environment. Use proper ventilation to remove vapors, mists and fumes or use proper respiratory protection as SCBA or supplied air.

### ACUTE:

INHALATION - Minimal odor present during normal material handling and use.

EYE CONTACT - Mild irritation, tearing, redness.

SKIN CONTACT - Mild irritation possible.

INGESTION - May cause mild gastrointestinal irritation, vomiting, nausea, & diarrhea.

CHRONIC:

Date Printed: 12/12/2007  
Product Code(s): 1221, 1225, 1229

Page: 5

---

Contains a possible human carcinogen.

Acute Toxicity Data: No data.

Carcinogenicity: NTP -No, IARC -No, OSHA -No  
This product has not been tested for carcinogenic effects. Some chemicals in this product may be identified by NTP, IARC and/or OSHA as carcinogenic, indicated above as "Yes". No further information available.

Teratology: No data.

Reproduction: No data.

Mutagenicity: No data.

---

## 12. ECOLOGICAL INFORMATION

No data.

---

## 13. DISPOSAL CONSIDERATIONS

This product when disposed represents a non-hazardous waste, as identified in 40CFR261. It is the responsibility of each waste generator to identify the proper classification of their waste streams.

---

## 14. TRANSPORT INFORMATION

The following transportation information is provided based on Transtar Autobody Technologies interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking and labeling prior to offering for transport.

USA (DOT) Status: Not regulated

Water (IMDG) Status: Not regulated

Air (ICAO, IATA) Status: Not regulated

Canada (TDG) Status: Not regulated

---

## 15. REGULATORY INFORMATION

The information listed in this section is not all inclusive of all regulations for this product or the chemical components of this product.

US Federal Regulations

TSCA Status: All known major components of this product are listed on the TSCA Inventory and/or are otherwise in compliance with TSCA.

Date Printed: 12/12/2007  
Product Code(s): 1221, 1225, 1229

Page: 6

---

SARA 302 (EHS) Status: No EHS chemicals present.

SARA 311/312 Status: No hazards to Emergency Responders identified.

SARA 313 Status: \* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

OSHA Status: This material meets the requirement of hazardous material and is subject to 29CFR1910.1200.

#### USA State Information

California Proposition 65: This product does not contain chemical(s) known to the State of California to cause cancer or birth defects or other reproductive harm.

Pennsylvania RtK Status: This material contains chemical(s) subject to notification under Pennsylvania Right to Know.

New Jersey RtK Status: This material contains chemical(s) subject to notification under New Jersey Right to Know.

Massachusetts RtK Status: This material contains chemical(s) subject to notification under Massachusetts Right to Know.

Rhode Island RtK Status: This material contains chemical(s) subject to notification under Rhode Island Right to Know.

#### International Regulations

##### Canada

DSL Status: All known major components of this product are listed on the DSL Inventory and/or are otherwise in compliance with the DSL

NDSL Status: Contains no chemicals on the NDSL

WHMIS: D2B

EINECS Status: All components of this material are listed on the EINECS Inventory.

---

#### 16. OTHER INFORMATION

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Transtar Autobody Technologies to be accurate. As with all chemicals, KEEP AWAY FROM CHILDREN AND ANIMALS. FOR PROFESSIONAL USE ONLY. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

---